

## ROOF PERMIT & ZONING CERTIFICATE 132 North Elmwood Avenue

**Application / Certificate** 

Permit Number	
---------------	--

Medina, OH 44256
Phone: 330-722-9030
www.medinaoh.org
permits@medinaoh.org

GENERAL	Property Location Lot #  PPN: TCOV Historic District  Estimated cost (omit cents) \$
CONTACT INFORMATION	Contractor/Applicant         Registration #
CT INFO	Phone Email Email Name Email E
CONTA	Address City State Zip         Phone Email
PROJECT INFORMATION	Type of improvement: New Addition Alteration Other  Type of installation: Tear off Lay Over (Only 1 lay over allowed)  Type of use:  Single Family Duplex Multi-family #Units Commercial Industrial Over Deck Garage Accessory Structure Describe if Other  If Commercial, Type of roof: Pitched Flat If flat, square footage:
SIGNATURE & SUBMITTAL	The owner or agent of the owner of this building and undersigned, do hereby covenant and agree to comply with all laws of the State of Ohio, Codified Ordinances of the City of Medina pertaining to the performance of work for which this permit is issued, and in accordance with the approved plans, specifications or manufacturer's instructions submitted herewith, and certify that the information and statements given on this application, drawings and specifications are to the best of their knowledge, true and correct. Undersigned accepts responsibility for requesting all required inspections in a timely manner.  Application By:  Signature of owner, contractor, or authorized agent  Print name of Applicant:  Print name of Applicant:
OFFICIAL USE ONLY	Fee \$    Signature: Date:   Zoning Official   Date:

## **ROOF GUIDELINES**

## GENERAL CODE INFORMATION FOR ROOF INSTALLATIONS

- Tear-off is required if the existing roof is water-soaked or deteriorated to the point that it is an inadequate base for additional roofing.
- Tear-off is required where the existing roof shingles are curled, or if the existing roof covering is wood shake, slate, clay, or cement/asbestos cement tiles.
- Tear-off is required with 2 or more layers of any type of roof covering.
- If rotted wood is encountered upon tear-off, please call for inspection before covering/replacing.
- All roof coverings shall be installed in accordance to the manufacturer's instructions.
- Ice protection is required starting from the edge of the eave or soffit to a minimum of 24 inches past the exterior wall line of the building. An inspection may be required. If required, a penalty for covering up without inspection may apply.
- Install underlayment (felt paper), per code.
- Provide adequate roof/attic ventilation, per code.
- Asphalt shingles shall be fastened to solidly sheathed decks.
- Flashings shall be installed to prevent moisture entering the wall and roof through joints and copings, through
  moisture permeable materials, and at wall and roof intersections, wherever there is a change in roof slope or
  direction, and around roof openings. Flashing against a vertical sidewall shall be by the step-flashing method.
- Call 24 hours in advance for ice protection, if required, and final inspections.